

TECH280P 4V - PNEUMATIC CONVEYOR



FOOD INDUSTRY



CHEMICAL-PHARMACEUTICAL



COFFEE, TEA, TOBACCO PROCESSING



WOOD



- ✓ Customization and configuration available according to specific needs
- ✓ Easy to install, turn on, use and sanitize
- ✓ No obstruction or environmental pollution
- ✓ CE-certified, FDA-certified system for food application. A wide range of optional accessories is available
- ✓ Increased productivity
- ✓ Product quality and integrity preservation
- ✓ Improved hygiene and operational conditions
- ✓ High efficiency Ventury system despite low energy consumption



SUCTION UNIT

Air supply pressure	bar	5 - 6
Max air flow	m ³ /h	85 - 110 - 130
Max water lift	mmH ₂ O	600 - 700 - 700
Q.ty of venturies□		4



FILTER UNIT

Air cleaning consumption□	NI/min	260 - 370 - 490
---------------------------	--------	-----------------



DISCHARGE UNIT

Ø Unload / Outlet □	mm	100
Type of unloading		Butterfly valve



LOADING UNIT

Weight	kg	22
Max load volume□	l	8
Ø P. conveying system □	mm	50 - 60
Dimensions	cm	Ø280 h770



SUCTION UNIT

High efficiency suction unit with Venturi vacuum pump and silencer



FILTER UNIT

Filter unit: an antistatic polyester bag for food application, FDA-certified, 1µm filter media.
Static and automatic filter cleaning system



DISCHARGE/LOAD UNIT

Single-piece truncated cone shape loading unit with tangential inlet
Unloading unit with butterfly valve



CONTROL UNIT

Control unit and pneumatic remote control placed 3 meters away from the loading unit



AVAILABLE ACCESSORIES

- ✓ FDA-Certified flexible hose
- ✓ Suction lance
- ✓ Pick-up hopper



OPTIONALS

- ✓ AISI316 STAINLESS STEEL COMPONENTS
- ✓ PNEUMATIC VIBRATOR
- ✓ RELIEF VALVE TO EMPTY THE PRODUCT LINE
- ✓ PARTS IN CONTACT WITH MIRROR POLISHING
- ✓ KIT FOR THE ASSEMBLY OR THE CONNECTION TO OTHER SYSTEMS